

# Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard  
280fil 1910.1200. Standard must be consulted for specific requirements.

## QUICK IDENTIFIER

Common Name: (used on label and list)

AutoMask Film - (Part Nos. 101, 102, 103, 104, 108,  
109, 111, 112 & 113)

WHEEL BAG MASKER - (Part Nos. 161, 161-0, 163,  
164, 167, 172, 176, 169 & 177)

MIRROR MASKER - (Part Nos. 165 & 170)

## Manufacturer's

Name	RBL Products, Inc.	Emergency
Address	6040 Russell	Telephone No. 1-800-584-8111
City, State and Zip	Detroit, Michigan 48211	Other Information
Signature of Person		Calls (313) 873-8806
Responsible for Preparation (Optional)		Date
		Prepared 1-4-93

## I. IDENTIFICATION

PRODUCT GROUP: Natural Pelleted Polyethylene Compounds

RESIN: Ethylene-Hexen Copolymer CAS NO: 25213-02-9

## II. PHYSICAL DATA

MELT INDEX: 0.005 - 200

DENSITY: 0.890 - 0.965

PERCENT VOLATILES BY VOLUME: Nil

APPEARANCE AND ODOR: Polyethylene film; whitish color; negligible odor.

## III. INGREDIENTS

HAZARDOUS COMPONENTS: NONE

AutoMask Masking Tape  
(Part Nos. 175-1, 175-2, 175-3)

An MSDS is not required by law for this product pursuant to OSHA regulations. Specifically, 29 CFR 1910.1200 (b) (6) (iv) indicates that "articles" are not applicable to the Hazard Communication section (1910.1200) of the OSHA regulations. AUTOMASK Masking Tape is considered to be "articles" as defined in 29 CFR 1910.1200 (c).

TRANSPARENT Fine-Line Tape  
(Part Nos. 151, 152)

## SECTION 2 - PRODUCT AND COMPONENT HAZARD DATA

A. COMPONENTS:	Approx. Percent	TLV**	CAS Reg. No.
Resin adhesive	35%		N/A
Polypropylene Film	65%		N/A

\*\*See Section VI-A for additional information on exposure limits.

## SECTION 3 - PHYSICAL DATA

- Appearance and Odor: Blue
- Boiling Point: Not applicable
- Softening Point: Approx. 200F (film)
- Specific Gravity: 1.05
- Vapor Pressure: Not applicable
- Percent Volatile by Volume: Not applicable
- Vapor Density (Air = 1): Not applicable
- Solubility in Water: Negligible

## SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

- Flash Point: 274C (525F)  
Method Used: Cleveland Open Cup
- Flammable Limits: Not applicable
- Extinguishing Agent: Water Spray, Dry Chemical, CO2
- Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.
- Unusual Fire and Explosion Hazards: Refer to NFPA Pamphlet No. 654, "Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical, and Plastics Industries", if this material is to be reduced to or collected as a powder.

## SECTION 5 - REACTIVITY DATA

- Stability: Stable
- Incompatibility: Oxidizing materials can cause a vigorous reaction
- Hazards Decomposition Products: As with any other organic material, combustion will produce carbon dioxide and probably carbon monoxide.
- Hazardous Polymerization: Will not occur.

## SECTION 6 - TOXICITY AND HEALTH

### A. EXPOSURE LIMITS

- OSHA Permissible Exposure Limit (PEL): Not established.
- Threshold Limit Value (TLV): Not established

### B. EXPOSURE EFFECTS

Inhalation: None expected

Eyes: None expected

### C. TOXICITY DATA

Toxicological findings for the major components used to formulate these products suggest they are of low toxicity.

## SECTION 7 - PERSONAL PROTECTION AND CONTROLS

- A. RESPIRATORY PROTECTION - None should be needed
- B. VENTILATION - General
- C. SKIN AND EYE PROTECTION -
- D. OTHER CONTROL MEASURE - None Required