

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard
29 CFR 1910.1200. Standard must be consulted for specific requirements.

QUICK IDENTIFIER

Common Name: (Used on label and list)

THE POLY BULLET

(Part Nos. 550, 560 & 570)

Manufacturer's Name:

RBL Products, Inc.

Address:

6040 Russell

City, State, Zip

Detroit, Michigan 48211

Emergency Telephone No.:

(800) 584-8111

Other Information Calls:

(313) 873-8806

Section I Identification

Polyethylene or Ethylene - Olefin Copolymer

497-98

Calcium Carbonate

40-03%

Does this product require reporting under SARA Title III? No

Do the components of this product comply with TSCA? Yes

Section II Hazards Identification

Inhalation: Negligible hazard at ambient temperature (-18 to +38 degrees C 0 to 100 degrees F).

Ingestion: Minimal toxicity.

Eye Contact: Minimal hazard.

Skin Contact: Negligible hazard at ambient temperature.

Section III First Aid Measures

Inhalation: In case of adverse exposure to vapors and/or aerosols formed at elevated temperatures, immediately remove the affected victim from exposure. Administer artificial respiration if necessary.

Keep at rest. Call for prompt medical attention.

Skin Contact: Minimal hazard.

Ingestion: First aid is not normally required.

Section IV Fire-Fighting Measures

Flash Point: 649 Deg. F. Note: Estimated Minimum

Flammable Limits: Not applicable

General Hazard

Solid material may burn at the flashpoint. If thermally decomposed, flammable/toxic gases may be released. Toxic gases will form upon combustion.

Fire Fighting

Use water to cool fire exposed surfaces, protect personnel, and extinguish the fire.

Respiratory and eye protection required for fire fighting personnel.

Decomposition Products Under Fire Conditions

Under Oxygen lean conditions. Carbon Monoxide (CO) and irritating smoke may be produced

Section V Stability and Reactivity

Section VI Toxicological Information

Please refer to Section III for available information on potential health effects.

Section VII Storage and Handling

Keep containers closed. Handle and open containers with care. Store in a cool, well ventilated place away from incompatible material. Do not handle or store near an open flame, heat or others sources of ignition.

Section VIII Disposal Measures

This product is non-hazardous as shipped. Refer to applicable federal, state and local regulations.

Section IX Transportation Information

This product is not a regulated substance under Department of Transportation (DOT) regulations.

Section X Hazard Rating Systems

This information is for people trained in:

National Paints & Coatings Association's (NPCA)

Hazardous Materials Identification System (HMIS)

National Fire Protection Association (NFPA 704)

Identification of the Fire Hazards of Materials

	NPCA-HMIS	NFPA	704	Key
Health	1	1		4 = Severe
Flammability	1	1		3 = Serious
Reactivity	0	0		2 = Moderate
				1 = Slight

Section XI Other Information

Notes:

Polymer CAS Numbers:

For polyethylene homopolymer grades: 9002-88-4

For ethylene/butene copolymer grades: 25087-34-7

For ethylene/hexene copolymer grades: 25213-02-9

Melting Point Ranges:

HDPE: 265 to 280 Deg F. (129 to 137.5 Deg C.)

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers.